

pH/ORP Transmitter

SELECTION GUIDE

MODEL 653	BASIC DESCRIPTION (pH/ORP MICROPROCESSOR TRANSMITTER)	
	Industrial input/output isolated pH/ORP transmitter with IP65 panel type ½ DIN housing. 4½ digit display selectable for pH or ORP, mV, temperature (°C or °F), current output and program messages. Precision ±1 digit (0.01 pH), stability ±2 digits (0.02 pH) per month. -2000 mV to 2000 mV, and -5 °C to 105 °C (23 °F to 221°F). Includes one instruction manual. Requires pH sensor temperature compensator option -34; sensor sold separately.	
	ADD	OPTIONS
	-5	24 VDC power supply; model 540 (115 VAC or 230 VAC ± 10 %, 50/60 Hz).
	-6	Intrinsic safe barrier, P/N A7900013
	-7	Wall mounting kit, P/N A2500268
	-8	2 inch pipe mounting kit, P/N A2500267
	-89	Stainless steel tag

Sample Order:

653	-8	pH Transmitter with pipe mount kit
-----	----	------------------------------------

DELIVERY estimate for 1-5 units
(quantity 6 & up, consult factory)

Stock to 10 weeks

653: Most Options

CALIBRATION AND SERVICE SUPPLIES

Please see pH Buffer and Calibration Kit Sheets