

X-Proof ppm D.O. Transmitter

PRICE/SELECTION GUIDE

MODEL 853-9	BASIC DESCRIPTION (D.O. 2-Wire Transmitter, Explosion-Proof)	
	Industrial input/output isolated dissolved oxygen transmitter with explosion-proof, class 1, division 1 barrel housing kit. 4-digit display selectable for D.O., temperature (°C or °F), current output and program messages. Precision ±1 digit and stability ±2 digits per month. 24 VDC 2-wire operated with one 4 mA to 20 mA output. Configurable 4 mA to 20 mA span, within 10 % to 100 % dissolved oxygen. Includes one instruction manual. Requires a D.O. sensor, sold separately, and a model 510 remote infra-red key pad (option -10).	
	ADD	OPTIONS
	-5	24 VDC power supply; model 540 (115 VAC or 230 VAC ± 10 %, 50/60 Hz).
	-6	Intrinsic safe barrier, P/N A7900013.
	-10	Model 510 infra-red remote control; intrinsically safe, operates one or more transmitters individually.
	-89	Stainless steel tag

Sample Order:

853-9	D.O. transmitter
-------	------------------

DELIVERY estimate for 1-5 units
(quantity 6 & up, consult factory)

Stock to 10 weeks

853-9: Most Options

CALIBRATION AND SERVICE SUPPLIES

Please see Dissolved Oxygen Solutions Sheet