

Free Available Cl₂ Sample Panel

SELECTION GUIDE

<p>MODEL 875-25</p>	<p><i>BASIC DESCRIPTION (Free Available Chlorine Sample Panel)</i></p> <p>Free available chlorine analyzer/controller, input/output isolated, with NEMA 4X enclosure. RS485 two way communication allows real-time log of calibration records, alarms, and current measurement. 4 ½ digit display, selects 0 ppm to 5 ppm chlorine, temperature, current output and program messages. RS485 and dual 4 mA to 20 mA DC outputs, programmable span from 10 % to 100 % and -5 °C to 105 °C (23 °F to 221°F). 115/230 VAC power, two assignable relays, SPDT 10 A, 115 V resistive. Includes sample conditioning panel with chlorine sensor, PRV, head tank, sample point, atmospheric drain, security and one instruction manual. Chlorine calibration kit, P/N A7010001, included. Needs no reagents.</p>	
	<i>ADD</i>	<i>OPTIONS</i>
	-34	Real time clock
	-35	Advanced, IC Net™ intelligence access program RS485. Refer to computer section, P/N IC2000.
	-52	Back lit display, green, P/N A9130023.
	-89	Stainless steel tag
	-95	Calibration kit refill P/N A7010002.
	-96	Precision, 0.001 ppm calibration kit, hand held portable colorimeter, P/N A7010004, requires option -97.
	-97	0.001 ppm calibration kit refill, 30 ampoules, for use with option -96, P/N A7010005.

Sample Order:

875-25	ppm free available chlorine analyzer with sample panel
--------	--

DELIVERY estimate for 1-4 units
(quantity 6 & up, consult factory)

2 to 4 Weeks 875-25: Most Options